

要項表

形式		容量(Ah)	外形図	外形寸法(約mm)				液面線高さ(約mm)		質量(約kg)	電解液量(約リットル)
ベント形	シール形	5時間率		W	L	H(最大)		A	B		
						ベント形	シール形				
AH20P	AH20PE	20	(1)	143	*52	272	332	183	30	2.9	0.9
AH30P	AH30PE	30	(1)	143	*52	272	332	183	30	3.2	0.7
AH40P	AH40PE	40	(1)	143	*52	272	332	183	30	3.4	0.5
AH50P	AH50PE	50	(1)	143	76	272	332	183	30	4.7	1.1
AH60P	AH60PE	60	(1)	145	100	280	332	183	30	6.1	1.6
AH80P	AH80PE	80	(1)	145	100	280	332	183	30	6.6	1.3
AH100P	AH100PE	100	(4)	170	120	370	441	245	40	11	3.2
AH120P	AH120PE	120	(4)	170	120	370	441	245	40	12	2.9
AH150P	AH150PE	150	(4)	170	120	370	441	245	40	13	2.6
AH200P	AH200PE	200	(6)	170	195	370	441	245	40	19	5.2
AH250P	AH250PE	250	(6)	170	195	370	441	245	40	21.5	4.4
AH300P	AH300PE	300	(7)	170	285	370	441	245	40	29	7.8
AH350P	AH350PE	350	(7)	170	285	370	441	245	40	31	7.2
AH400P	AH400PE	400	(7)	170	285	370	441	245	40	32.5	6.7
AH450P	AH450PE	450	(8)	170	390	370	441	245	40	43.5	10
AH500P	AH500PE	500	(8)	170	390	370	441	245	40	45	9.5
AH600P	AH600PE	600	(8)	170	515	372	-	245	40	56	13.5
AH700P	AH700PE	700	(8)	170	515	372	-	245	40	60	12

*シール形の長さ寸法は52にセル間隔5を加え合計57となります。