

要項表

形式		容量(Ah)	外形図	外形寸法(約mm)				液面線高さ(約mm)		質量(約kg)	電解液量(約リットル)
ベント形	シール形	5時間率		W	L	H(最大)		A	B		
						ベント形	シール形				
AM20P	-	20	(1)	76.5	48.5	268	-	164	40	1.5	0.3
AM30P	AM30PE	30	(1)	143	*52	272	332	183	30	2.8	0.9
AM40P	AM40PE	40	(1)	143	*52	272	332	183	30	2.9	0.8
AM50P	AM50PE	50	(1)	143	*52	272	332	183	30	3	0.7
AM60P	AM60PE	60	(1)	143	76	272	332	183	30	4.1	1.2
AM80P	AM80PE	80	(1)	143	76	272	332	183	30	4.5	1.1
AM100P	AM100PE	100	(1)	145	100	272	362	183	30	6	1.5
AM120P	AM120PE	120	(1)	145	100	272	362	183	30	6.3	1
AM150P	AM150PE	150	(4)	170	120	370	441	245	40	9.5	3.2
AM200P	AM200PE	200	(4)	170	120	370	441	245	40	10	2.8
AM250P	AM250PE	250	(6)	170	195	370	441	245	40	16	5.4
AM300P	AM300PE	300	(6)	170	195	370	441	245	40	18	5
AM350P	AM350PE	350	(6)	170	195	370	441	245	40	19	4.6
AM400P	AM400PE	400	(7)	170	195	370	441	245	40	21.5	3.8
AM450P	AM450PE	450	(7)	170	285	370	441	245	40	25.5	7.8
AM500P	AM500PE	500	(7)	170	285	370	441	245	40	27	7
AM600P	-	600	(8)	170	390	370	-	245	40	36	10.3
AM700P	-	700	(8)	170	390	370	-	245	40	37.5	9.5
AM800P	-	800	(8)	170	390	370	-	245	40	39	8.7
AM900P	-	900	(8)	170	515	372	-	245	40	48	13
AM1000P	-	1000	(8)	170	515	372	-	245	40	50	12

*シール形の長さ寸法は52にセル間隔5を加え合計57となります。